





# CoMax Ink Series

Introduction	CoMax consistently achieves high quality printing effects and is designed to minimize environmental pollution for a better working environment. CoMax is the highest & premium grade ink among DY product ranges.
Characteristics	ISO 2846-1 Color Compliance / Soy Oil Based Inks Excellent Gloss / Fast Setting & Drying / Stay Open Type
Substrates	Coated & Matt & Cardboard Papers
Packaging	1 kg / 2 kg Tin Can

Test Data								
Item Code & Name	Tack	Viscosity	Gloss	Pigmentation (Density)	Light Fastness	Protection of Environment & Health		
	(400rpm)	(S.M)			By Blue Wool Scale	RoHS	Heavy Metal	SVHC
CM-1 Magenta	9.5-10.5	60-62	80↑	18.5%	5	Pass	Pass	Pass
CM-3 Yellow	8-9	62-63	75↑	11.5%	4	Pass	Pass	Pass
CM-5 Cyan	10-11	61-62	80↑	18%	8	Pass	Pass	Pass
CM-8 Black	7.5-8.5	61-62	80↑	23%	8	Pass	Pass	Pass

※ Tack : Value at 400 rpm by Ink-O-Meter / Viscosity : Dong Yang Spread-O-Meter(10 Sec) / Gloss : Gloss Meter at 60 °angle  
 ※ Actual tack and viscosity is affected by ink film thickness, press speed, fountain solution and general conditions of pressroom

Dong Yang Ink	338-6 Kagok-Ri Jinwi-Myun Pyungtaek-City Kyungki-Do Rep. of Korea (trad@dongyangink.com) Tel. : 82-31-6609-210~7, Fax : 82-31-667-4877	
Padi Insumos Graficos	AV FEDERALISMO NORTE 511 PLANTA BAJA RFC PIG-100310-LR7, COL. ARTESANOS, C.P. 44200 GUADALAJARA, JAL. MEXICO	



**DONG YANG INK**